

AMENDMENTS TO THE CLAIMS

1. (Currently Amended) A fitting and pipe section assembly that is capable of being installed in tubing of a jetted bath to render the tubing adaptable to accept a close fit device, comprising:

a pipe section having a center segment integrally formed with inlet and outlet end portions of the pipe section for fluid flow coupling to an inlet and an outlet of the tubing;

first and second fittings integrally formed ~~disposed on the inlet and outlet end portions of the pipe section, the first and second fittings facing one another;~~

wherein the center segment of the pipe section may be selectively removed leaving the inlet and outlet end portions including the first and second fittings; and

wherein the center segment may be replaced with a close fit device by coupling the close fit device to the first and second fittings.

~~wherein the pipe section may accept the close fit device between the inlet and outlet portions of the pipe section.~~

2. (Original) The fitting and pipe section assembly of Claim 1, wherein the pipe section includes first and second indicia on the pipe section that guide post-installation cutting of the pipe section at predetermined points and removal of the center segment so that the fitting and pipe section assembly may accept a close fit device between the remaining portions of the fitting and pipe section assembly.

3. (Currently Amended) The fitting and pipe section assembly of Claim 1, wherein the fitting and pipe section assembly is an integral unitary ~~unitary~~-body.

4. (Previously Presented) The fitting and pipe section assembly of Claim 1, wherein the close fit device may be removably secured to the fittings by a fastening assembly.

LAW OFFICES OF
CHRISTENSEN O'CONNOR JOHNSON KINDNESS^{PLLC}
1420 Fifth Avenue
Suite 2800
Seattle, Washington 98101
206.682.8100

5. (Original) The fitting and pipe section assembly of Claim 4, wherein the fastening assembly comprises a union nut and a split nut retainer.

6. (Previously Presented) The fitting and pipe section assembly of Claim 4, wherein the close fit device has an inlet and an outlet with flanges positioned at the inlet and outlet; wherein the fastening assembly comprises an outer seal which may be positioned between the fitting and the flange, a split nut which may be tightened upon the fitting by rotating the split nut, and a nut cover which may be slid over the tightened split nut.

B, 7. (Original) The fitting and pipe section assembly of Claim 1, wherein the close fit device is selected from the group consisting of a heater, ozone generator, chemical dispenser, fragrance dispenser, filter, pump, valve, flow meter, or water softener.

8. (Original) The fitting and pipe section assembly of Claim 1, wherein the fitting and pipe section is further capable of being installed with a transverse tubing segment of a jetted bath, wherein the fitting and pipe section assembly further comprises a "T" junction; wherein the pipe section includes an inlet and outlet at the longitudinal ends of the pipe section and an aperture there between; and wherein a transverse pipe branch defining a port extends perpendicular to the pipe section from the aperture.

9. (Original) The fitting and pipe section assembly of Claim 8, wherein the transverse pipe branch may be removably fastened to a transverse tubing segment of the jetted bath.

10. (Original) A fitting and pipe section assembly that is capable of being installed in tubing of a jetted bath to render the tubing adaptable to accept a close fit heater device, comprising:

a pipe section having a center segment between inlet and outlet end portions for fluid flow coupling to an inlet and an outlet of the tubing;

first and second fittings disposed on the inlet and outlet portions of the pipe section;
wherein the pipe section includes first and second indicia on the pipe section that guide post-installation cutting of the pipe section at predetermined points;

wherein the center segment of the pipe section may be selectively removed from the pipe section by cutting at the first and second indicia, leaving the inlet and outlet portions including the first and second fittings; and

wherein the fitting and pipe section assembly may accept the close fit device between the inlet and outlet portions of the fitting and pipe section assembly.

81 11. (Original) The fitting and pipe section assembly of Claim 10, wherein the close fit device may be secured to the fittings by a first and second fastening assembly.

12. (Original) The fitting and pipe section assembly of Claim 10, wherein the fitting and pipe section assembly is a unitary body.

13. (Original) The fitting and pipe section assembly of Claim 11, wherein the close fit device may be removably secured to the first and second fittings by the first and second fastening assembly.

14. (Original) The fitting and pipe section assembly of Claim 13, wherein the fastening assembly comprises a union nut and a split nut retainer.

15. (Original) The fitting and pipe section assembly of Claim 13, wherein the close fit device has an inlet and an outlet with flanges positioned at the inlet and outlet; wherein the fastening assembly comprises an outer seal which may be positioned between the fitting and the flange, a split nut which may be placed over the flange and the fastening structure and tightened by rotating the split nut, and a nut cover which may be slid over the tightened split nut.

16. (Original) The fitting and pipe section assembly of Claim 10, wherein the close fit device is selected from the group consisting of a heater, ozone generator, chemical dispenser, fragrance dispenser, filter, pump, valve, flow meter, or water softener.

17. (Original) The fitting and pipe section assembly of Claim 10, wherein the fitting and pipe section is further capable of being installed with a transverse tubing segment of a jetted bath, wherein the fitting and pipe section assembly further comprises a "T" junction; wherein the pipe section includes an inlet and outlet at the longitudinal ends of the pipe section and an aperture there between; and wherein a transverse pipe branch defining a port extends perpendicular to the pipe section from the aperture.

18. (Original) The fitting and pipe section assembly of Claim 17, wherein the transverse pipe branch may be removably fastened to the transverse tubing segment of the jetted bath.

19. (Original) The fitting and pipe section assembly of Claim 17, wherein the first and second indicia comprise annular grooves.


20-22. (Canceled)

23. (Currently Amended) A fitting and pipe section assembly and interchangeable heater device for mounting in fluid flow communication in tubing of a jetted bath, comprising:

a pipe section having a center segment integrally formed with inlet and outlet end portions of the pipe section, each of the end portions carrying a first close fit fitting integrally formed with the end portion, wherein the first close fit fittings face one another, the inlet and outlet end portions being adapted to be coupled in fluid flow communication to an inlet and outlet of the tubing to install the pipe section in the tubing; and

a heater device having a tubular body defining an inlet end and an outlet end, each of the inlet and outlet ends carrying a second close fit fitting, wherein the center segment can be


selectively laterally removed from between the inlet and outlet end portions and the heater device can then be laterally inserted in place of the center segment between the inlet and outlet end portions of the pipe section, wherein the second close fit fittings of the heater device engaging the first close fit fittings of the pipe section without displacement of the installed inlet and outlet end portions of tubing.

 24. (Previously Presented) A fitting and pipe section assembly that is capable of being installed in tubing of a jetted bath to render the tubing adaptable to accept a close fit device, comprising:

(a) a pipe section having a center segment disposed between inlet and outlet end portions for fluid flow coupling to an inlet and an outlet of the tubing, wherein the pipe section includes first and second indicia on the pipe section that guide post-installation cutting of the pipe section at predetermined points and removal of the center segment; and

(b) first and second fittings disposed on the inlet and outlet portions of the pipe section; wherein the center segment of the pipe section may be selectively removed leaving the inlet and outlet portions including the first and second fittings; and

wherein the fitting and pipe section assembly may accept the close fit device between the inlet and outlet portions of the fitting and pipe section assembly.

 25. (New) The fitting and pipe section assembly of Claim 1, wherein the first and second fittings each include an engagement surface adapted to couple to a fitting of a close fit device, wherein when the center segment is coupled to the tubing, the engagement surfaces are disengaged from any fitting.